



EQ8207TL Equipment

<ul style="list-style-type: none"> • G.V.W.R.-14,000 # • G.A.W.R.(Each Axle) - 7,000 # • Coupler - 2 - 5/16" adjustable • Safety Chain - 3/8" grade 43 with hooks • Jack - 10,000 # drop leg • Crossmembers - 3" channel • Wheel Covers - 11ga. diamond plate • Tongue - 8" channel full frame • Bed width - 96" • 4' Dovetail • Side rails - 5" channel with stake pockets 	<ul style="list-style-type: none"> • Axles - 2-7,000 # cambered brake axles • Suspension - slipper spring with equalizer • Tires - ST 235 / 80R 16" load range E • Wheel - 16" 8 bolt white spoke • Deck - 2" pressure treated pine • Lights - D.O.T. stop, tail, turn, and clearance • Elec. Plug - 7-way RV • Paint - High solids acrylic enamel • Ramps - 5' stand up • Sealed modular wiring harness
--	--

Standard Features

Optional Features

<ul style="list-style-type: none"> • 16" White spoke • Pressure treated decking • Electric breakaway • E-Z lube brake axles • 4' Dovetail 	<ul style="list-style-type: none"> • Steel deck or steel dove tail • Gooseneck • Boxed end
--	---

Dimensions

Length	A	B	C	D	E
18'	216"	128"	46.5"	30"	96"
20'	240"	140"	46.5"	30"	96"
22'	264"	152"	46.5"	30"	96"

