



LS Utility Series

• G.V.W.R. - 2,900 #	• Axles - 3,500 # cambered E-Z lube
• G.A.W.R. - 3,500 #	• Suspension - Multi-leaf spring
• Coupler - 2"	• Tires - 205-75-15" load range C
• Safety Chain - 3/16" grade 30 with hooks	• Wheel - 15" 5 bolt white spoke
• Jack - top wind	• Deck - 2" pressure treated pine
• Frame - 3"x2"x 3/16" angle	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - top 3"x2"x3/16 angle	• Elec. Plug - 4-way flat
• Fenders - 9"x32" roll formed with backs	• Paint - High solids acrylic enamel
• Deck height 20"	

Standard Features Optional Features

• 15" white spoke rims	• 24" sides
• Pressure treated decking	• Expanded metal sides
• Light protectors	• Slatted sides
• E-Z Lube axles	• Swing up jacks

Dimensions

Trailer size	A	B	C	D	E
5X8'	96"	55.5	38.5	20"	60"
5X10'	120"	69.5	38.5	20"	60"
5X12'	144"	86.5"	38.5	20"	60"
5X14'	168"	98.5"	38.5	20"	60"
6X10'	120"	69.5"	38.5	20"	76"
6X12'	144"	86.5"	38.5	20"	76"
6X14'	168"	100"	38.5	20"	76"

